Network Digital Signage Player



Overview

The MP-02 video playback system offers digital signage capabilities in a compact network- capable package. Interface with new customers through dynamic signage or download online data- it's all possible with the MP-02. The MP-02 Network MPEG playback system can store and load DVD quality audio and video (MPEG 1/2/4, MP3, JPEG) from compact flash cards up to 4GB, perfect for broadcasting solutions.

The MP-02 online features make it the video playback system with the most flexibility and its quality manufacturing guarantees reliability for information kiosks, dynamic signage, and other video playback tasks.

Features

- Various video codecs and card formats supported
- Multi-language support
- MP3 playback capability

Options

■ VESA Mount Bracket

Specifications

Hardware

ESS chipset Video Output / Audio Output 12V On board EEPROM memory

I/O

VGA, S-Video, Composite Video Stereo phone jack USB 1.1 port Compact Flash reader

Data Rates

Data Nates			
Format	VCD	AVI/Divx	AVI/Divx
Resolution	352x240	720x480	640x480
NTSC/PAL	352x288	720x576	640x480
Video Compression	MPEG 1	MPEG 2	MPEG 4
Video Bitrate	1150kbps	MPEG	MPEG

Mechanical and Environment

Single Voltage +12V/1A w/ ACPI function support Operation Temperature: 0~60°C [32~140°F] Humidity: 85% maximum 144 x 85 x 25 mm [5.67 x 3.35 x .098 inch] 365 g [0.80 lbs]

Audio / Video Support

2 channel audio DAC MPEG 1/2/4, MP3, JPEG, AVI

